

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet
Issue Date: 27-Mar-2013
A317LP

CHEMWATCH 35-1585
Version No:2.1.1.1
CD 2013/1 Page 1 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ARDEX WATERPROOFING DETAIL TAPE

PRODUCT USE

Detail tape for use with Ardex liquid applied membrane.

SUPPLIER

Company: Ardex Australia Pty Ltd
Address:
20 Powers Road
Seven Hills
NSW, 2147
Australia
Telephone: 1800 224 070
Emergency Tel: 1800 224 070 (Mon- Fri, 9am- 5pm)
Fax: +61 2 9838 7817

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

RISK

•None under normal operating conditions.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
Tape consisting of		
calcium carbonate	471-34-1	<70
isoprene/ isobutene copolymer (butyl rubber)	9010-85-9	<20
hydrocarbons, C6- 20, hydrogenated, polymers	69430-35-9	<20
lubricating oils, petroleum C24- 50, solvent- extract	101316-72-7	<10

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- If this product comes in contact with eyes:
 - Wash out immediately with water.
 - If irritation continues, seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet
Issue Date: 27-Mar-2013
A317LP

CHEMWATCH 35-1585
Version No:2.1.1.1
CD 2013/1 Page 2 of 13
Section 4 - FIRST AID MEASURES

SKIN

- If skin or hair contact occurs:
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes, aerosols or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Slight hazard when exposed to heat, flame and oxidisers.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Combustible.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Heating calcium carbonate at high temperatures(825 C.) causes decomposition, releases carbon dioxide gas and leaves a residue of alkaline lime.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

None

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Secure load if safe to do so.
- Bundle/collect recoverable product.
- Collect remaining material in containers with covers for disposal.

MAJOR SPILLS

- Minor hazard.
- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet
Issue Date: 27-Mar-2013
A317LP

CHEMWATCH 35-1585
Version No:2.1.1.1
CD 2013/1 Page 3 of 13

Section 6 - ACCIDENTAL RELEASE MEASURES

- Wear physical protective gloves e.g. Leather.
- Contain spill/secure load if safe to do so.
- Bundle/collect recoverable product and label for recycling.
- Collect remaining product and place in appropriate containers for disposal.
- Clean up/sweep up area.
- Water may be required.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- No smoking, naked lights, heat or ignition sources.
- Keep dry.
- Store under cover.
- Protect containers against physical damage.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA mg/m ³	Notes
Australia Exposure Standards	Ardex Waterproofing Detail Tape (Calcium carbonate (a))	10	(see Chapter 14)
Australia Exposure Standards	Ardex Waterproofing Detail Tape (Oil mist, refined mineral)	5	

The following materials had no OELs on our records

- isoprene/ isobutene copolymer (butyl rubber): CAS:9010- 85- 9
- hydrocarbons, C6- 20, hydrogenated, polymers: CAS:69430- 35- 9

MATERIAL DATA

ARDEX WATERPROOFING DETAIL TAPE:

- None assigned. Refer to individual constituents.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 4 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

CALCIUM CARBONATE:

- For calcium carbonate:

The TLV-TWA is thought to be protective against the significant risk of physical irritation associated with exposure.

ISOPRENE/ ISOBUTENE COPOLYMER (BUTYL RUBBER):

- for isoprene:

Russian OEL STEL: 40 mg/m³

CEL TWA: 50 ppm, 139 mg/m³ (compare WEEL TWA)

(CEL = Chemwatch Exposure Limit)

Saturated vapour concentration: 724000 ppm at 25 C.

Odour Threshold Value: 0.005 ppm

The workplace environmental exposure level (WEEL) established by the AIHA is thought to be protective against respiratory tract irritation and against potential subacute and subchronic effects reported in several studies.

TLV TWA: 0.001 mg/m³ (as total proteins) Inhalable fraction skin sensitiser

as rubber processing fume:

MEL-TWA: 0.6 mg/m³ as cyclohexane solubles [HSE, UK]

BRMA-TWA: 0.25 mg/m³ as cyclohexane solubles [BRMA Code of Practice]

Rubber fume is a complex and indeterminate mixture of substances and is defined as "fume evolved in the mixing, milling and blending of natural rubber and synthetic polymers combined with chemicals, and in the processes which convert the resultant blend into finished products or parts thereof, and including any inspection procedures where fume continues to be evolved".

"Fume" generally describes solid particles generated by chemical reactions, or by condensation from the gaseous state, usually after volatilisation from melted substances, and often accompanied by a chemical reaction such as oxidation or thermal breakdown.

Several chemical agents may occur in rubber fume which are experimental or animal carcinogens, however, given the number of chemicals used or formed during rubber making, difficulties arise in attributing a particular effect to a given exposure.

Stomach cancer has been associated with work in jobs early in the production line; lung and lower oesophagus cancer with all work processes; and lymphomas with jobs where co-exposure to solvents occurs. Other cancers have also been reported with liver tumours appearing as a secondary phenomenon. No no-effect levels have been determined.

Two studies showed no excess of bladder cancer in workers entering the industry after 1950: the excess risk before that date is thought to result from exposure to residual beta-naphthylamines previously used as anti-oxidants.

as rubber process dust:

MEL-TWA: 6 mg/m³ [HSE, UK]

Rubber process dust is a complex, variable mixture of particulates defined as "dust arising in the stages of rubber manufacture where ingredients are handled, weighed, added to or mixed with natural or synthetic elastomers. It does not include dusts arising from the abrasion of cured rubber but occurs during the preparation of compounds of either synthetic or natural rubber.

There is some evidence that occupational exposure to rubber dusts produces an excess incidence of stomach cancer. HSE data concluded that there was a small but significant excess of stomach cancer associated with the initial processes in rubber manufacture. Stomach cancer shows a marked social class gradient, which may lead to an over-estimation of the risk.

One report from the USA stated that exposure in rubber processing areas produces pulmonary disease but this has not been supported by UK epidemiology nor reports from the industry.

No no-effect level has been determined. The MEL was considered appropriate because it was felt reasonably practical for industry to comply with this value.

HYDROCARBONS, C6-20, HYDROGENATED, POLYMERS:

■ These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 5 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility,
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the

rigorous skin cleansing procedures necessary for their removal. [ACGIH]

This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations

but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or poorly soluble* in water or, preferably, in aqueous lung fluid (if data is available)

and

- have a low toxicity (i.e.. are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload).

LUBRICATING OILS, PETROLEUM C24-50, SOLVENT-EXTRACT:

- Toxicity and Irritation data for petroleum-based mineral oils are related to chemical components and vary as does the composition and source of the original crude.

A small but definite risk of occupational skin cancer occurs in workers exposed to persistent skin contamination by oils over a period of years. This risk has been attributed to the presence of certain polycyclic aromatic hydrocarbons (PAH) (typified by benz[a]pyrene).

Petroleum oils which are solvent refined/extracted or severely hydrotreated, contain very low concentrations of both.

NOTE L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. European Union (EU) List of Dangerous Substances (Annex I) - up to the 29th ATP.

for mineral oils, excluding metal working fluids, poorly and mildly refined:

A2; Suspected Human Carcinogen (ACGIH)

A2 is used primarily when there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals with relevance to humans.

PERSONAL PROTECTION

EYE

- No special equipment for minor exposure i.e. when handling small quantities.

• OTHERWISE:

- Safety glasses with side shields.

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

- No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.

- Barrier cream.

- Eyewash unit.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet
Issue Date: 27-Mar-2013
A317LP

CHEMWATCH 35-1585
Version No:2.1.1.1
CD 2013/1 Page 6 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATOR

• Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Grey solid tape with a characteristic odour; insoluble in water.

PHYSICAL PROPERTIES

Does not mix with water.

Sinks in water.

State	Manufactured	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Applicable
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	Not Applicable	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	>200	Vapour Pressure (kPa)	Not Applicable
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	1.55
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Applicable
Volatile Component (%vol)	Not Applicable	Evaporation Rate	Not Applicable

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet
Issue Date: 27-Mar-2013
A317LP

CHEMWATCH 35-1585
Version No:2.1.1.1
CD 2013/1 Page 7 of 13

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Considered an unlikely route of entry in commercial/industrial environments.

EYE

- Not normally a hazard due to physical form of product.
The dust may produce eye discomfort causing smarting, pain and redness.

SKIN

- Not normally a hazard due to physical form of product.

INHALED

- Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

- This manufactured article is considered to have low hazard potential if handling and personal protection recommendations are followed.

TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

LUBRICATING OILS, PETROLEUM C24-50, SOLVENT-EXTRACT:
ISOPRENE/ ISOBUTENE COPOLYMER (BUTYL RUBBER):

- No significant acute toxicological data identified in literature search.

ARDEX WATERPROOFING DETAIL TAPE:
Not available.

CALCIUM CARBONATE:

TOXICITY

Oral (Rat) LD50:6450 mg/kg

IRRITATION

Skin (rabbit):500 mg/24h- Moderate

Eye (rabbit):0.75 mg/24h - SEVERE

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 8 of 13

Section 11 - TOXICOLOGICAL INFORMATION

HYDROCARBONS, C6-20, HYDROGENATED, POLYMERS:

TOXICITY

Oral (rat) LD50:>5000 mg/kg

Dermal (Rat) LD50:>2000 mg/kg *

* [Eastman]

IRRITATION

Eye (rabbit - washed):slight

LUBRICATING OILS, PETROLEUM C24-50, SOLVENT-EXTRACT:

■ The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives;

The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:

- The adverse effects of these materials are associated with undesirable components, and
- The levels of the undesirable components are inversely related to the degree of processing;
- Distillate base oils receiving the same degree or extent of processing will have similar toxicities;
- The potential toxicity of residual base oils is independent of the degree of processing the oil receives.
- The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.

Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential carcinogenic and mutagenic activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Mutagenicity and carcinogenicity testing of residual oils has been negative, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size.

Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. Numerous tests have shown that a lubricating base oil's mutagenic and carcinogenic potential correlates with its 3-7 ring polycyclic aromatic compound (PAC) content, and the level of DMSO extractables (e.g. IP346 assay), both characteristics that are directly related to the degree/conditions of processing.

for Unrefined and Mildly Refined Distillate Base Oils

Acute toxicity: LD50s of >5000 mg/kg (bw) and >2g/kg (bw) for the oral and dermal routes of exposure, respectively, have been observed in rats dosed with an unrefined light paraffinic distillate. The same material was also reported to be "moderately irritating" to the skin of rabbits. When tested for eye irritation in rabbits, the material produced Draize scores of 3.0 and 4.0 (unwashed/washed eyes) at 24 hours, with the scores returning to zero by 48 hours. The material was reported to be "not sensitising" when tested in guinea pigs

Repeat dose toxicity: 200, 1000 and 2000 mg/kg (bw)/day of an unrefined base oil has been applied undiluted to the skin of male and female rabbit.. The test material was applied to the rabbits' skins 3 times/week for 4 weeks. To ensure maximum exposure, the applied material was covered with an occlusive dressing for 6 hours. In the high dose group, body weight gains were affected by treatment. These effects were largely due to effects on growth rate during the first week of the study. There were no significant differences between treated and control groups for any of the recorded haematological and clinical chemistry values. Gross and microscopic pathology findings relating to the treated skin were seen in all rabbits in the highest dose group. The findings consisted of "slight" to "moderate" proliferative changes in the treated skin.

Reproductive/ developmental toxicity No reproductive or developmental toxicity studies have been reported for unrefined & mildly refined distillate base oils. However, a developmental toxicity screening study has been reported for heavy vacuum gas oil, a material with a process history similar to the unrefined distillate base oils.. As an unrefined vacuum distillate material, heavy vacuum gas oil contains the broadest spectrum of chemical components and highest concentration of bioavailable and/or biologically active components. Because of their lack of or low level of processing, in comparison to other refined base oils, the unrefined lubricating base oils will also have higher concentrations of bioavailable and/or biologically active components.

Heavy vacuum gas oil was applied daily to the skin of pregnant rats on days 0-19 of gestation. Dose levels administered included: 30, 125, 500 and 1000 mg/kg (bw)/day. All animals were euthanised on day 20. In the dams, the only dose-related finding at gross necropsy was pale colored lungs in four animals in the highest dose group and in one animal in the 500 mg/kg (bw)/day group. Mean thymus weights of the dams in the highest

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 9 of 13

Section 11 - TOXICOLOGICAL INFORMATION

dose group were approximately half those of the control groups. Although absolute liver weights were unaffected by exposure to the gas oil, mean relative liver weights were increased (approximately 15%) in groups exposed to doses greater than 125 mg/kg (bw)/day. Maternal and foetal body weights were reduced at 500 and 1000 mg/kg (bw)/day. Significant increases in resorptions were also seen in these two dose groups. Soft tissue variations and malformations, and skeletal malformations were also increased at 500 and 1000 mg/kg. Genotoxicity: Modified Ames assays have been carried out on a number of base oils that were either unrefined or poorly refined. The oils were found to be mutagenic, with a strong correlation between mutagenicity and 3-7 ring PAC content.

Carcinogenicity: The general conclusions that can be drawn from the animal carcinogenicity studies are potential skin carcinogens. When applied repeatedly to the skin, carcinogenic base oils are associated only with skin tumours and not with an increase in systemic tumours.

SKIN

calcium carbonate	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	0
-------------------	--	-------------------------------	---

Section 12 - ECOLOGICAL INFORMATION

LUBRICATING OILS, PETROLEUM C24-50, SOLVENT-EXTRACT:

CALCIUM CARBONATE:

- DO NOT discharge into sewer or waterways.

CALCIUM CARBONATE:

- For Metal:

Atmospheric Fate - Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air.

Environmental Fate: Environmental processes, such as oxidation, the presence of acids or bases and microbiological processes, may transform insoluble metals to more soluble ionic forms. Environmental processes may enhance bioavailability and may also be important in changing solubilities.

Aquatic/Terrestrial Fate: When released to dry soil, most metals will exhibit limited mobility and remain in the upper layer; some will leach locally into ground water and/ or surface water ecosystems when soaked by rain or melt ice. A metal ion is considered infinitely persistent because it cannot degrade further. Once released to surface waters and moist soils their fate depends on solubility and dissociation in water. A significant proportion of dissolved/ sorbed metals will end up in sediments through the settling of suspended particles. The remaining metal ions can then be taken up by aquatic organisms. Ionic species may bind to dissolved ligands or sorb to solid particles in water.

Ecotoxicity: Even though many metals show few toxic effects at physiological pH levels, transformation may introduce new or magnified effects.

LUBRICATING OILS, PETROLEUM C24-50, SOLVENT-EXTRACT:

- for lubricating oil base stocks:

Vapor Pressure Vapor pressures of lubricating base oils are reported to be negligible. In one study, the experimentally measured vapour pressure of a solvent-dewaxed heavy paraffinic distillate base oil was 1.7×10^{-4} Pa. Since base oils are mixtures of C15 to C50 paraffinic, naphthenic, and aromatic hydrocarbon isomers, representative components of those structures were selected to calculate a range of vapor pressures. The estimated vapor pressure values for these selected components of base oils ranged from 4.5×10^{-1} Pa to 2×10^{-13} Pa. Based on Dalton's Law the expected total vapour pressure for base oils would fall well below minimum levels (10^{-5} Pa) of recommended experimental procedures.

Partition Coefficient (log Kow): In mixtures such as the base oils, the percent distribution of the hydrocarbon groups (i.e., paraffins, naphthenes, and aromatics) and the carbon chain lengths determines in part the partitioning characteristics of the mixture. Generally, hydrocarbon chains with fewer carbon atoms tend to have lower partition coefficients than those with higher carbon numbers. However, due to their complex composition, unequivocal determination of the log Kow of these hydrocarbon mixtures cannot be made. Rather, partition coefficients of selected C15 chain-length hydrocarbon structures representing paraffinic, naphthenic, and aromatic constituents in base oil lubricants were modelled. Results showed typical log Kow values from 4.9 to 7.7, which were consistent with values of >4 for lubricating oil basestocks

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 10 of 13

Section 12 - ECOLOGICAL INFORMATION

Water Solubility:When released to water, base oils will float and spread at a rate that is viscosity dependent. While water solubility of base oils is typically very low, individual hydrocarbons exhibit a wide range of solubility depending on molecular weight and degree of unsaturation. Decreasing molecular weight (i.e., carbon number) and increasing levels of unsaturation increases the water solubility of these materials. As noted for partition coefficient, the water solubility of lubricating base oils cannot be determined due to their complex mixture characteristics. Therefore, the water solubility of individual C15 hydrocarbons representing the different groups making up base oils (i.e., linear and branched paraffins, naphthenes, and aromatics) was modelled. Based on water solubility modelling of those groups, aqueous solubilities are typically much less than 1 ppm. (0.003-0.63 mg/l)

Environmental Fate:

Photodegradation: Chemicals having potential to photolyse have UV/visible absorption maxima in the range of 290 to 800 nm. Some chemicals have absorption maxima significantly below 290 nm and consequently cannot undergo direct photolysis in sunlight (e.g. chemicals such as alkanes, alkenes, alkynes, saturated alcohols, and saturated acids). Most hydrocarbon constituents of the materials in this category are not expected to photolyse since they do not show absorbance within the 290-800 nm range. However, photodegradation of polyaromatic hydrocarbons (PAHs) can occur and may be a significant degradation pathway for these constituents of lubricating base oils. The degree and rate at which PAHs may photodegrade depend upon whether conditions allow penetration of light with sufficient energy to effect a change. For example, polycyclic aromatic compounds (PAC) compounds bound to sediments may persist due to a lack of sufficient light penetration

Atmospheric gas-phase reactions can occur between organic chemicals and reactive molecules such as photochemically produced hydroxyl radicals, ozone and nitrogen oxides. Atmospheric oxidation as a result of radical attack is not direct photochemical degradation, but indirect degradation. In general, lubricating base oils have low vapour pressures and volatilisation is not expected to be a significant removal mechanism for the majority of the hydrocarbon components. However, some components (e.g., C15 branched paraffins and naphthenes) appear to have the potential to volatilise. Atmospheric half-lives of 0.10 to 0.66 days have been calculated for representative C15 hydrocarbon components of lubricating base oils

Stability in Water: Chemicals that have a potential to hydrolyze include alkyl halides, amides, carbamates, carboxylic acid esters and lactones, epoxides, phosphate esters, and sulfonic acid esters. Because lubricating base oils do not contain significant levels of these functional groups, materials in the lubricating base oils category are not subject to hydrolysis

Chemical Transport and Distribution in the Environment : Based on the physical-chemical characteristics of component hydrocarbons in lubricating base oils, the lower molecular weight components are expected to have the highest vapour pressures and water solubilities, and the lowest partition coefficients. These factors enhance the potential for widespread distribution in the environment. To gain an understanding of the potential transport and distribution of lubricating base oil components, the EQC (Equilibrium Criterion) model was used to characterize the environmental distribution of different C15 compounds representing different structures found in lube oils (e.g., paraffins, naphthenes, and aromatics). The modelling found partitioning to soil or air is the ultimate fate of these C15 compounds. Aromatic compounds partition principally to soil. Linear paraffins partition mostly to soil, while branching appears to allow greater distribution to air. Naphthenes distribute to both soil and air, with increasing proportions in soil for components with the greater number of ring structures. Because the modelling does not take into account degradation factors, levels modelled in the atmosphere are likely overstated in light of the tendency for indirect photodegradation to occur.

Biodegradation: The extent of biodegradation measured for a particular lubricating oil basestock is dependent not only on the procedure used but also on how the sample is presented in the biodegradation test. Lubricant base oils typically are not readily biodegradable in standard 28-day tests. However, since the oils consist primarily of hydrocarbons that are ultimately assimilated by microorganisms, and therefore inherently biodegradable. Twenty-eight biodegradability studies have been reported for a variety of lubricating base oils. Based on the results of ultimate biodegradability tests using modified Sturm and manometric respirometry testing the base oils are expected to be, for the most part, inherently biodegradable. Biodegradation rates found using the modified Sturm procedure ranged from 1.5 to 29%. Results from the manometric respirometry tests on similar materials showed biodegradation rates from 31 to 50%. Biodegradation rates measured in 21-day CEC tests for similar materials ranged from 13 to 79%.

Ecotoxicity:

Numerous acute studies covering fish, invertebrates, and algae have been conducted to assess the ecotoxicity of various lubricating base oils. None of these studies have shown evidence of acute toxicity to aquatic organisms. Eight, 7-day exposure studies using rainbow trout failed to demonstrate toxicity when tested up to the maximum concentration of 1000 mg/L applied as dispersions. Three, 96-hour tests with rainbow trout also

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 11 of 13

Section 12 - ECOLOGICAL INFORMATION

failed to show any toxic effects when tested up to 1000 mg/L applied as dispersions. Similarly, three 96-hour tests with fathead minnows at a maximum test concentration of 100 mg/L water accommodated fractions (WAF) showed no adverse effects. Two species of aquatic invertebrates (*Daphnia magna* and *Gammarus* sp.) were exposed to WAF solutions up to 10,000 mg/L for 48 and 96-hours, respectively, with no adverse effects being observed. Four-day exposures of the freshwater green alga (*Scenedesmus subspicatus*) to 500 mg/L WAF solutions failed to show adverse effects on growth rate and algal cell densities in four studies

Multiple chronic ecotoxicity studies have shown no adverse effects to daphnid survival or reproduction. In 10 of 11 chronic studies, daphnids were exposed for 21 days to WAF preparations of lubricating base oils with no ill effects on survival or reproduction at the maximum concentration of 1000 mg/L. One test detected a reduction in reproduction at 1000 mg/L. Additional data support findings of no chronic toxicity to aquatic invertebrates and fish. No observed effect levels ranged from 550 to 5,000 mg/L when tested as either dispersions or WAFs.

The data described above are supported by studies on a homologous series of alkanes. The author concluded that the water solubility of carbon chains .C10 is too limited to elicit acute toxicity. This also was shown for alkylbenzene compounds having carbon numbers .C15. Since base oils consist of carbon compounds of C15 to C50, component hydrocarbons that are of acute toxicological concern are, for the most part, absent in these materials. Similarly, due to their low solubility, the alkylated two to three ring polyaromatic components in base oils are not expected to cause acute or chronic toxicity. This lack of toxicity is borne out in the results of the reported studies.

The effects of crude and refined oils on organisms found in fresh and sea water ha been extensively reviewed. sea water. Where spillages occur the non-mobile species suffer the greatest mortality, whereas fish species can often escape from the affected region. The extent of the initial mortality depends on the chemical nature of the oil, the location, and the physical conditions, particularly the temperature and wind velocity. Most affected freshwater and marine communities recover from the effects of an oil spill within a year. The occurrence of biogenic hydrocarbons in the world's oceans is well recorded. They have the characteristic isoprenoid structure, and measurements made in water columns indicate a background concentration of 1.0 to 10 ul/l. The higher molecular weight materials are dispersed as particles, with the highest concentrations of about 20 ul/l occurring in the top 3 mm layer of water.

A wide variation in the response of organisms to oil exposures has been noted. The larvae of fish and crustaceans appear to be most susceptible to the water-soluble fraction of crude oil. Exposures of plankton and algae have indicated that certain species of diatoms and green algae are inhibited, whereas microflagellates are not.

For the most part, molluscs and most intertidal worm species appear to be tolerant of oil contamination.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
calcium carbonate	No Data Available	No Data Available	No Data Available	No Data Available
isoprene/ isobutene copolymer (butyl rubber)	No Data Available	No Data Available	No Data Available	No Data Available
hydrocarbons, C6- 20, hydrogenated, polymers	No Data Available	No Data Available	No Data Available	No Data Available
lubricating oils, petroleum C24- 50, solvent- extract	No Data Available	No Data Available	No Data Available	No Data Available

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 12 of 13

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

calcium carbonate (CAS: 471-34-1,13397-26-7,15634-14-7,1317-65-3) is found on the following regulatory lists;

"Acros Transport Information", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Quarantine and Inspection Service List of chemical compounds that are accepted solely for use at establishments registered to prepare meat and meat products for the purpose of the Export Control Act 1982", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix C", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "Australia Therapeutic Goods Administration (TGA) Substances that may be used as active ingredients in Listed medicines", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Numbering System for Food Additives", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information"

isoprene/ isobutene copolymer (butyl rubber) (CAS: 9010-85-9) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)"

hydrocarbons, C6-20, hydrogenated, polymers (CAS: 69430-35-9) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information"

lubricating oils, petroleum C24-50, solvent-extract (CAS: 101316-72-7) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "OECD List of High Production Volume (HPV) Chemicals"

No data for Ardex Waterproofing Detail Tape (CW: 35-1585)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
calcium carbonate	471- 34- 1, 13397- 26- 7, 15634- 14- 7, 1317- 65- 3

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering

continued...

ARDEX WATERPROOFING DETAIL TAPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Mar-2013

A317LP

CHEMWATCH 35-1585

Version No:2.1.1.1

CD 2013/1 Page 13 of 13

Section 16 - OTHER INFORMATION

controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 27-Mar-2013

Print Date: 27-Mar-2013

This is the end of the MSDS.